

ZAMTAS

SLIM NG SERIES HI-FLUX LED TRAFFIC LIGHT

Developed over the past few decades by ZAMTAS International's engineering teams in Australia, Pakistan and China, ZAMTAS' Slim NG Series Hi-Flux 300 mm LED Universal Traffic Light combines the functionality of the standard traffic light with the enhanced power savings of the latest technologies of LED lighting.

The Slim NG Series Hi-Flux traffic lights can be provided in a variety of arrangements and sizes, subject to legislative requirements and the clients' needs.



KEY FEATURES

- Highly efficient LEDs enhance power savings
- Dimming function allows even further power savings
- Highly aesthetic workmanship + modern and slim design
- The separate system controller is fully-SCATS compatible
- Available in 12 / 24V DC & 110 / 230V AC working voltages
- Modular, Vandal-proof design
- Suitable for inductive loop sensors
- Dust-proof, IP65 rated
- Simplicity of assembling and servicing
- Single and double mounting using brackets
- Also available in 100 and 200mm diameter specification



STANDARDS

- *EN 12368 : 2006 - Traffic control equipment – Signal heads
- *EN 50293 : 2000 Electromagnetic compatibility - Road traffic signal systems
- *EN 55022 : 1998 + A1 : 2000 + A2 : 2003, CISPR 22 : 2005 - Conducted and Radiated Emissions
- *EN 50293 : 2000 - Road traffic signal systems. Electromagnetic compatibility



ZAMTAS

T R A F F I C S Y S T E M S

Slim NG Series Hi-Flux 300mm LED Traffic Light



www.zamtas.com.au
www.zamtastraffic.com.au

Slim NG Series Hi-Flux 300mm LED Traffic Light



Product Specifications

Number of aspects	Dimensions w x h x d [mm]	Material	Assembly	Temperature class	Resistance
2-way	358x743x130	UV stabilized polycarbonate	Double or single support with brackets. Assembly of screens with use of self-tapping screws.	A, B and C in compliance with EN 12368	In compliance with EN 12368
3-way	358x1113x130	UV stabilized polycarbonate	Double or single support with brackets. Assembly of screens with use of self-tapping screws.	A, B and C in compliance with EN 12368	In compliance with EN 12368

Technical Specifications

Body housing material	Poly carbonate (PMMA), Sun visor included Optical lens, showing a very good colour uniformity
Size	300mm (12") diameter Aspect arrangement 2 / 3 / as required
Luminous intensity (cd)	Red: 726cd Yellow: 1090cd Green: 682cd
Luminance Uniformity	Lmin:Lmax < 1:10
Colour Chromaticity (Typical – varies depending on exact model)	Red: X-0.699,Y-0.301 Yellow: X-0.571, Y-0.426 Green: X-0.082,Y-0.559
Viewing Angle	Compliant with the $\pm 30^\circ$ requirements as per EN 12368:2006
Operating temperature range	Between -43°C and 74°C
Operating Voltage	110V AC / 230V AC / 12V DC / 24V DC Low-Voltage compliant
Typical Power consumption	11W
Moisture Ingress	IP65 – complaint to IEC 60529:1989 + A1:1999 (2001-2)
Power Factor	>0.91
Phantom Class	>3
Life span	70,000 hours (8 years of continuous light)
Impact resistance	compliant with EN60598-1
Certifications	CE certified RoHS certified

NG SERIES HI-FLUX 300mm LED TRAFFIC LIGHT



ZAMTAS International is a market leading innovator for design, supply and service of energy efficient lighting, automation products and solar systems.

ZAMTAS is renowned for its safe and environmentally effective products that fulfill the requirements of our clients in Australia, Asia and Middle East, based on the belief that a package should save more time and money than its cost.

We provide high quality products at competitive prices backed by the highest standard of technical service to achieve total customer satisfaction

ZAMTAS

TRAFFIC SYSTEMS

Phone: +61 2 9682 6224
Fax: +61 2 9682 3308
E-mail: info@zamtas.com.au

5/16-28 Martha Street
Clyde NSW 2124
www.zamtas.com.au
www.zamtastraffic.com.au